

PURCHASED
COMPONENT
KEY FEATURES


DESCRIPTION OF REQUIREMENTS
DIMENSIONAL REQUIREMENTS (AS SHOWN ON DRAWING)
N/A
LOAD/RATING REQUIREMENT
N/A
MATERIAL REQUIREMENT
N/A
PACKAGING REQUIREMENT
N/A
OTHER REQUIREMENTS
Input Voltage: 12VDC 10.5V - 16.5V) Continuous Output Power: 3000w (+/-3%) Output Voltage: 100/110/115/120 VAC (+/-5%) (Dip Switch Selectable) Output Waveform: Pure Sign Wave (THD<5%@ normal load) Operating Temp: -25C to approx. 40C Safety Standard: Certified UL 458 (UL only for GFCI) SURGE RATING 150% OF CONTINUOUS POWER FOR 3 SECONDS EMC STANDARDS FCC CLASS B: TS400, TS700, TS1000, AND TS1500 FCC CLASS A: TS2000 AND TS3000 EFFICIENCY 90%–93% STANDBY RECOVERY FIVE SECONDS



THIS DRAWING IS THE PROPERTY OF ADRIAN STEEL COMPANY AND IS NOT TO BE USED IN ANY MANNER
DETRIMENTAL TO THE INTERESTS OF ADRIAN STEEL COMPANY

TOLERANCES & INSPECTION			RELEASE & REVISIONS	
UNLESS OTHERWISE SPECIFIED			INITIAL ECN:	22984
ALL BEND ANGLES ARE 90 DEGREES			CURRENT ECN:	22984
ALL DIMENSIONS ARE IN INCHES.			ECN DESCRIPTION:	
REFERENCE DIMENSIONS (X.XXX) DO NOT REQUIRE INSPECTION			ADD PPDS	
FEATURES	HOLES/SLOTS	ANGLES		
0.0 = ± .125	0.0 = ± .062	0° = ± 2°		
0.00 = ± .062	0.00 = ± .031	0.0° = ± 1°		
0.000 = ± .031	0.000 = ± .015			
Material Thickness: per ASTM Std. Weld Callouts per AWS			REVISED BY: MJF	

PURCHASED COMPONENT
REFERENCED SUPPLIER AND/OR MANUFACTURER
Vanner
REFERENCED SUPPLIER AND/OR MANUFACTURER PART NUMBER
TS12-3000
COLOR (ONLY LIST IF COLOR SPECIFIC)
COMODITY ITEM (Y/N) (YES = ALL DIMENSIONS AND NOTES ARE REFERENCE) (NOTE: DIMENSIONS AND FEATURES MAY VARY FOR A COMODITY ITEM.)
NO

PRINTED DOCUMENT IS UNCONTROLLED			Sheet 1 of 1
PART / PRODUCT IDENTIFICATION			
<div> ADRIAN STEEL®</div>		ADRIAN STEEL COMPANY 906 JAMES STREET, ADRIAN, MI 49221	
MAT'L USED:		DESIGNED BY: MJF	REVISION LEVEL A
DESCRIPTION: INV TS12-3000			
WEIGHT (Lbs.): 18.5	SEGMENT CODE: EIN	PART NUMBER: 56907	