

FASTENER GROUPS LISTED BELOW ARE USED FOR ASSEMBLY AND INSTALLATION. SOME ASSEMBLY DRILLING IS REQUIRED. FASTENERS SHOULD BE OF A GRADE 5 OR 8, AND SHOULD BE THE TYPE FOR OUTDOORS USE. STAINLESS STEEL FASTENERS WILL WORK THE BEST FOR THIS PRODUCT.

SYM.	FASTENERS	QTY
------	-----------	-----

INSTALLATION FASTENERS BAGLS4

(4)	1/4-20 ELASTIC L'NUT S/S
(2)	1/4 PLAIN FLAT WASHER S.S.
(2)	1/4-20 × 2×2-1/2 U-BOLT SS
(2)	1/4-20×2-1/8×2-1/2 sq. U-BOLT



ADRIAN STEEL CO.
906 JAMES STREET
ADRIAN, MI 49221
517/265-6194

LS 4
K.D. LADDER STOP KIT
LOAD RUNNER LADDER RACKS

DWG BY	ECN#	DATE	CHK'D BY	PACKAGE#	ISS.
JLC	12861	4/26/2010		S/L LS4	D
PACKAGE WEIGHT-		104 #	REFERENCE: REF 25640		
ITEM	PART NO.	DESCRIPTION		QTY.	

1	19749	LADDER STOP POST, ND FAS		1	
---	-------	--------------------------	--	---	--

(D) REMOVED SC NOTE

INSTALLATION PROCEDURE:

- 1) LOCATE DESIRED POSITION FOR LADDER STOP POST.
- 2) SELECT REQUIRED U-BOLTS:
 - USE (R) (ROUND) FOR INSTALLATION ON FRONT NOSE.
 - USE (S) (SQUARE) FOR INSTALLATION ON ALL OTHER POSITIONS
 - DISCARD UNUSED U-BOLTS
- 3) SLIDE U-BOLTS AROUND TUBING.
- 4) TIGHTEN NUTS.

